

## Clear Quartz Halogen lamps

IR 300W CL SK15 230V

**0033020**



### Range Features

- Features
- Tubular envelope made from transparent clear quartz
- Transmits the full spectrum of visible and infrared radiation
- Clear lamps are the most efficient for transmitting infrared energy
- Instant on-off capability
- 
- Applications
- The glare from the visible light component restricts these to industrial applications, eg Drying of paints in tunnels and automotive body shops
- Heating of plastics for PET bottle blowing
- High speed drying in paper production mills
- Drying of lacquers and printing inks
- Baking and curing of powder coatings
- Thermal sterilisation



### PRODUCT OVERVIEW

|                          |               |
|--------------------------|---------------|
| Colour temperature (K)   | 2550          |
| EAN code                 | 5410288330204 |
| Cap/Base                 | SK15          |
| Watt (Nominal) (W)       | 300           |
| Ordering number          | 0033020       |
| Average life (Rated) (h) | 2000          |
| Voltage (V)              | 230           |

### DATA TABLE

#### General data

|                  |               |
|------------------|---------------|
| Burning position | Horizontal    |
| EAN code         | 5410288330204 |
| Cap/Base         | SK15          |
| Ordering number  | 0033020       |

## Clear Quartz Halogen lamps

IR 300W CL SK15 230V

**0033020**

|                                 |  |
|---------------------------------|--|
| <b>Range features</b>           | <b>Features</b><br>Tubular envelope made from transparent clear quartz<br>Transmits the full spectrum of visible and infrared radiation<br>Clear lamps are the most efficient for transmitting infrared energy<br>Instant on-off capability  |
|                                 | <b>Applications</b><br>The glare from the visible light component restricts these to industrial applications, eg Drying of paints in tunnels and automotive body shops<br>Heating of plastics for PET bottle blowing<br>High speed drying in paper production mills<br>Drying of lacquers and printing inks<br>Baking and curing of powder coatings<br>Thermal sterilisation |
| <b>Product name</b>             | IR 300W CL SK15 230V   |
| <b>Average life (Rated) (h)</b> | 2000   |
| <b>Sales pack quantity</b>      | 1  |

### Optical data

|                               |      |
|-------------------------------|------|
| <b>Colour temperature (K)</b> | 2550 |
|-------------------------------|------|

### Electrical data

|                           |     |
|---------------------------|-----|
| <b>Watt (Nominal) (W)</b> | 300 |
| <b>Voltage (V)</b>        | 230 |

### Physical data

|   |                       |
|---|-----------------------|
| <b>Single packaging type</b>                      | Blister               |
| <b>Weight (kg)</b>                                | 0.02                  |
| <b>Outer package net weight (kg)</b>              | 1.05                  |
| <b>Single product net weight (kg)</b>             | 0.02                  |
| <b>Outer packaging weight (kg)</b>                | 1.56                  |
| <b>Single packaging weight (kg)</b>               | 0.03                  |
| <b>Outer package gross weight (kg)</b>            | 2.61                  |
| <b>Single product gross weight (kg)</b>           | 0.05                  |
| <b>Outer package volume (dm3)</b>                 | 19.544                |
| <b>Single package volume (dm3)</b>                | 0.283                 |
| <b>Units per outer package</b>                    | 50                    |
| <b>Outer package dimensions (L x W x H) (cm)</b>  | 29.50 x 26.50 x 25.00 |
| <b>Single package dimensions (L x W x H) (cm)</b> | 4.40 x 4.40 x 14.60   |

## Clear Quartz Halogen lamps

IR 300W CL SK15 230V

**0033020**

### TECHNICAL DRAWINGS

