

Slit Illumination Head and accessories



- ⋆ **Solid metal construction.** Will last a lifetime.
- ⋆ **Slit instrument head.** Simplifies the use of instruments.
- ⋆ **Fiber optics illumination.** Bright, homogeneous light.
- ⋆ **Multi-coated, scratch-resistant swivel lens with 1.6x magnification.** High-resolution image.
- ⋆ **Simple open construction.** Easy to clean and disinfect with conventional solutions.
- ⋆ **Double bayonet lock for specula.** Specula mounted firmly by double lock.

Slit Illumination Head	2.5V	3.5V
with swivel lens	<b>G-001.21.301</b>	<b>G-002.21.301</b>
XHL Xenon Halogen spare bulb	<b>X-001.88.077</b>	<b>X-002.88.078</b>
Swivel lens	<b>G-000.21.209</b>	

Long, closed specula



For use with the Slit Illumination Head.

- ⋆ **Metal construction, chrome-plated.** Easy to clean, disinfect and sterilize.
- ⋆ **Double bayonet lock for specula.** Firm mounting of specula to head.

Closed specula for Slit Illumination Head	
57 mm long / 4 mm dia.	<b>G-000.21.330</b>
65 mm long / 6 mm dia.	<b>G-000.21.331</b>
90 mm long / 7 mm dia.	<b>G-000.21.332</b>
150 mm long / 10 mm dia.	<b>G-000.21.350</b>

57 mm 65 mm 90 mm 150 mm  
 4 mm dia. 6 mm dia. 7 mm dia. 10 mm dia.

Slit metal specula, open



For use with the Slit Illumination Head.

- ⋆ **High-quality chrome-plated metal construction.** Easy to clean, disinfect and sterilize.
- ⋆ **Matt internal surfaces.** Reduced reflexes.
- ⋆ **60° opening with rounded edges.** Ideal for instrumentation, atraumatic insertion.
- ⋆ **Double bayonet fitting.** Positive fit.

Slit metal specula for Slit Illumination Head	
65 mm long / 6 mm dia.	<b>G-000.21.341</b>
90 mm long / 7 mm dia.	<b>G-000.21.342</b>

65 mm long 90 mm long  
 6 mm dia. 7 mm dia.