

XBO 7000 W/HS XL OFR

XBO Xtreme Life | Xenon short-arc lamps for cinema projection



Product benefits

- Short arc with very high luminance for brighter screen illumination
- Constant color temperature of 6,000 K throughout the entire lamp lifetime
- Easy to maintain
- High arc stability
- Instant light on screen thanks to hot restart function
- Wide dimming range

Product features

- Wattage: 1,200...8,000 W



May 16, 2017, 00:37:34 XBO 7000 W/HS XL OFR

Product datasheet

Technical data

Electrical data

Nominal wattage	7000.00 W	
Lamp voltage	42 V	
Nominal current	160 A	
Lamp current	160 A	
Current control range	110165 A	

Dimensions & weight

Diameter	78.0 mm
Length	436.0 mm
Length with base excl. base pins/connection	393.00 mm
Light center length (LCL)	170.5 mm ¹⁾
Electrode gap cold	11.0 mm
Cable/wire length, input side	400 mm
Product weight	1025.00 g

1) Distance from end of base to tip of electrode (cold)

Temperatures & operating conditions

Max. permitted ambient temp. pinch point	230 °C
--	--------

Lifespan

1.10	(50)
Lifespan	65U n
	05011

Additional product data

Base anode (standard designation)	SFaX30-9.5
Base cathode (standard designation)	SFa30-7.9

Product datasheet

Capabilities

Cooling	Forced ¹⁾
Burning position	p15/s15 ²⁾

$^{1)}$ Vertical and horizontal

²⁾ For vertical burning position: anode (+) on top

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321412928	OSRXB07000HSXL	-	-	-

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321412928	XBO 7000 W/HS XL OFR	Shipping carton box 1	590 mm x 229 mm x 234 mm	31.62 dm³	2111.30 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.